



STRONG  
AND RELIABLE  
SINCE 1960



STROS - Sedlčanské  
strojířny, a.s.

Phone: +971 502827857

E-mail: info@stros.ae

www.stros.cz

# Light Material Hoist ALULIFT 200



## DESCRIPTION:

- Low weight
- Quick assembly
- Economical
- Modular system
- Connection to a standard 230V house network
- Lifting height can be changed in the range of 2m up to a maximum height of 60m
- The purchase price depends on the required Lifting height of the hoist

The Alulift construction hoist is a light material hoist with a load capacity of up to 200kg and is intended for the transport of material on construction sites with a small or medium scope of work. It is used by both small and large construction companies.

It significantly saves time for transporting building materials and increases safety on the construction site. The ALULIFT construction hoist can be connected to a standard 230V house network with 16A protection.

Alulift is very popular for its easy and quick assembly and also for a very affordable price. This aluminum hoist is supplied as a kit, so the individual components can be purchased or combined gradually. The base of the hoist is a ladder mast with a power unit at the bottom. The hoist car is raised and lowered using the carrying rope and pulley at the top of the hoist.

Technical data	ALULIFT 200 V	ALULIFT 200 S
Load capacity	200 kg	
Lifting speed	25 m/min	
Lifting height	max. 60 m	max. 19 m
Rope (diameter / length)	6.3 mm / 43 m, 63 m, 83 m, 125 m	
Voltage system	1 PEN 50 Hz 230 V	
Control voltage	24 V AC	
Electric motor power	1.5 kW	

Mast ties and top mast overhang		
Mast height (m)	Mast tie spacing (m)	Top mast overhang (m)
60	2	1



Alulift 200 V



Alulift 200 S

